

Air Impact Wrenches



2145QIMAX 3/4" ■ Short anvil



- 1,830 Nm of maximum torque in reverse
- Ergonomic composite housing is lightweight, protects from cold air and offers great operator comfort
- The low weight of this tool will reduce operator fatigue
- 360° swivel inlet helps eliminate twisted hoses
- Two-year warranty

Also available
2145QIMAX-3
 Long anvil 75 mm
2145QIMAX-6
 Long anvil 150 mm

Protection Boot
2145M-BOOT
 CCN: 48385033

Ref.	CCN	in	Nm	Nm	rpm	bpm	kg	mm	in	mm	mm	mm	mm	l/s	l/s	dB(A)	m/s/K ⁽¹⁾
2145QIMAX	45624327	3/4"	1,830	1,220	6,300	1,150	3.35	217	3/8 NPT	13	4.0	15.10	96.3	4.0	15.10	96.3	8.7/2.7
2145QIMAX-3	47119524	3/4"	1,830	1,220	6,300	1,150	3.79	293	3/8 NPT	13	4.0	15.10	96.3	4.0	15.10	96.3	8.1/1.2
2145QIMAX-6	47121454	3/4"	1,830	1,220	6,300	1,150	4.23	369	3/8 NPT	13	4.0	15.10	96.3	4.0	15.10	96.3	8.1/1.2

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.
 Performance at 6.2 bar (90 psi)

Air Impact Wrenches | 3/4"

2161XP 3/4" ■ Short anvil



- 1,695 Nm
- Only 5.4 kg (2161XP)
- Twin-hammer impact mechanism
- Steel hammer case
- 3-position power regulator

Also available
2161XP-6
 Long anvil 150 mm

Protection Boot
2161-BOOT
 CCN: 45505401

261 3/4" ■ Short anvil



- 1,491 Nm
- Jumbo-hammer impact mechanism
- Steel hammer case
- 5-position power regulator

Also available
261-3
 Long anvil 75 mm
261-6
 Long anvil 150 mm

Protection Boot
261-BOOT
 CCN: 45505468

259 3/4" ■ Short anvil



- 1,424 Nm
- Only 4.0 kg and 218 mm
- Swinging-hammer impact mechanism
- 2-position power regulator

Protection Boot
259-BOOT
 CCN: 45661899

Ref.	CCN	in	Nm	Nm	rpm	bpm	kg	mm	in	mm	mm	mm	mm	l/s	l/s	dB(A)	m/s/K ⁽¹⁾
2161XP	01372085	3/4"	1,695	1,356	6,000	1,025	5.35	216	3/8 NPT	13	4.7	21.50	94.7	4.7	21.50	94.7	9.8/1.8
2161XP-6	01372093	3/4"	1,695	1,356	6,000	1,025	5.94	370	3/8 NPT	13	4.7	21.50	94.7	4.7	21.50	94.7	9.8/1.8
261	01209798	3/4"	1,491	813	5,500	1,000	5.62	224	3/8 NPT	13	4.5	17.90	98.1	4.5	17.90	98.1	10.4/1.3
261-3	01211101	3/4"	1,491	813	5,500	1,000	5.90	300	3/8 NPT	13	4.5	17.90	98.1	4.5	17.90	98.1	10.4/1.3
261-6	01217199	3/4"	1,491	813	5,500	1,000	6.21	376	3/8 NPT	13	4.5	17.90	98.1	4.5	17.90	98.1	10.4/1.3
259	45631918	3/4"	1,424	1,085	6,500	1,000	4.00	218	3/8 NPT	10	3.8	14.20	91.6	3.8	14.20	91.6	6.4/0.8

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.
 Performance at 6.2 bar (90 psi)