

# TG8 TEQ-GRINDER / POLISHER



Made in USA

For use by:

- Tile & stone contractors
- Floor Preparation
- Rental Stores
- Public Works
- Municipalities
- Coating contractors
- Shot blasting specialists
- Concrete repair contractors

## Features:

- Available with either a grinding disc or TEQ-Lok plate
- Low profile allows the TG8 to grind under cabinet toe kicks
- Longer wheelbase to maximize the head weight, geared down for lower rpm with increased torque and longer arc swing and operator leverage for very aggressive grinding action
- Dual size vacuum port for 2" and 3" vacuum hoses
- Adjustable handle with bolted joint to maintain its rigidity. Handle folds down for compact storage and easy transport in car trunks.
- Welded steel frame construction with tough powder coat finish
- Large 8" grey non-marking wheels
- Heavy duty flexible coupler for fast grinding of rough and uneven slab surfaces
- Rubber skirt slips on or off without tools

## Ideal for:

- Coating removal including epoxies, polyaspartics, urethanes, paints, thinset, cut back adhesives, and sealers.
- Grinding smooth rough concrete surfaces
- Leveling uneven or curling slabs
- Grinding hard surfaces, feather edging sidewalks and gutters, high and uneven joints and similar surfaces
- Stock removal to lower surface height
- Polishing concrete
- Very aggressive grinding with many tooling options to customize the machine for maximum performance.



TEQ-Lok Plate 160222 and  
D91003 Grinding Disc



## TG8 Grinder / Polisher

Disc Size	8"	8"
Motor/Engine	2hp	5.5 Honda
Phase	Single	Gas
Full Load AMPS @115V	18.4	GXV160
RPM - Disc	2800	2800
Model	FGE 2L	FGG 5H
Height	37"	37"
Length	37"	37"
Width	20"	20"
Weight	130 lbs	120 lbs
Part No. w/Grinding Plate	G00046	G00048
Part No. w/TEQ-Lok Plate	G00057	G00058
<i>Grinding disc is D91003 TEQ-Lok plate is 160222 Standard rotation is RH (right hand)</i>		

## Standard TG8 Grinding Tools/Accessories

Diameter & Width	Seg	Grit	Part No.
FGG34 8"x3/4"* (std bond)	10	Coarse - 30/40	D91003
FGP35 8"x3/4"* (std bond)	10	Med - 60/80	D91005
FGG36 8"x3/4"* (hard bond)	10	Coarse - 30/40	D91009
FGG34 8"x3/4"* (std bond)	5	Coarse - 30/40	D91006
<i>*includes rubber isolator 161113</i>			

Discover the DITEQ  
*Difference!*



DITEQ Corporation 9876 Pflumm Road, Lenexa, KS 66215  
Telephone: 866-688-1032 Fax: 877-220-4777 www.diteq.com